



1318



Tally DASCOM's 1318 flat-bed serial dot matrix printer, is a 9 pin, 80 column printer with USB and parallel interfaces as standard. The 1318 is ideal for front office applications in retail outlets, travel agents, train stations, banks and doctor's office where space is limited.

With high quality output, an easy to use control panel and the option to use pre-cut or tractor fed paper, the 1318 is ideal for counter-top printing applications such as, tickets, receipts, forms and multipart documents.

Compact in size and low on cost

- Compact 9-pin flat-bed printer
- Up to 240 characters per second
- Ideal for front office applications
- Easy to use
- Long life ribbon
- Small footprint

The long life ribbon of the 1318 means fewer ribbon changes, less downtime and lower running costs.

With print speeds of 240 characters per second (cps) and flexible media handling it keeps transactions smooth and the user happy.

The 1318 is a reliable and easy to use printer, with low running costs and a space saving size.

Available Configuration:

1318 Standard Product

SERIAL MATRIX PRINTERS

MOBILE PRINTERS

THERMAL PRINTERS

LINE MATRIX PRINTERS

LASER PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

1318

Print Speed	10 cpi: 240 cps (HSD), 180 cps (Draft), 45 cps (NLQ) 12 cpi: 200 cps (HSD), 216 cps (Draft). 54 cps (NLQ)
Print Method	Flat-Bed Serial Impact Dot Matrix
Resolution	Up to 144 x 240 dpi
Throughput (ECMA 132)	TBD pages per hour
Character Density	10, 12, 15, 17.1, 20cpi, Proportional Spacing
Line Density	1, 2, 3, 4, 6, 8 lpi
Printhead life	400 Million Strokes per pin
Memory	64 kB
Standard Connectivity	USB 2.0 and parallel (Bi-directional)
Standard Emulation	Epson (ESC P/2), IBM 2380+
Fonts	Draft, Roman, Sans Serif, 8 Barcodes
Consumables	Black Ribbon: 7 million characters
Standard Paper Handling	Friction and push tractor
Number of Copies	Original +4 (5-part forms)
Paper Type	Cut sheet and continuous forms
Paper Weight	42-90 gsm
Paper Size	76,2 to 269,2 mm wide
Physical Weight	5,5 kg
Physical Size	(HxWxD): 202x420x342
Power Voltage	230 V / 50 to 60 Hz
Power Consumption	max 7,5 W in Stand by
Reliability MTBF	10.000 hours
Drivers	Windows 2000, 2003 Server, XP, Vista, Windows 7
Temperature	0°C to +45°C
Humidity	10% to 80% (not condensing)
Acoustic	< 49dB(A) (ISO 7779)

Note NB: For OCR applications it is recommended that your readers are tested with print samples supplied by DASCOM prior to purchase. Paper is a highly variable medium and should be tested prior to purchase. The quoted consumable life is the average for the printer when used under normal operation conditions.



DASCOM AP Pte. Ltd.

63 Hillview Avenue #08-22 Lam Soon Industrial Building • Singapore 669569
Tel.: +65 6760-8833 • Fax: +65 6760-1066
sales@dascom.com.sg • www.dascom.com.sg

SERIAL MATRIX PRINTERS
MOBILE PRINTERS
THERMAL PRINTERS
LINE MATRIX PRINTERS
LASER PRINTERS